



MODEL L32, L33, & L35



FEATURES/BENEFITS:

- 10 AWG Solid/Stranded capability for high current applications
- 2-, 3-, & 5-Port options to address just about any application
- Low lever force may reduce risk of repetitive trauma injury
- Wide wire range for easy installation at OEM and in Field
- Transparent shell enables easy verification of connection
- Ground rating eliminates need for special "ground" connector

ELECTRICAL:

VOLTAGE:

General: 600V Max.
 Signs/Luminaires: 1000V Max.
 Amperage: 30A (41A IEC 60998)

MECHANICAL:

Compact size to fit into confined junction boxes
 Wide levers ease actuation
 Profiled housing for improved grip
 Reusable solid and stranded wire

PHYSICAL:

HOUSING: PC (Transparent)
 LEVERS: Nylon
 Contacts: Copper
 Plating: Tin
 Temperature: 105°C (221°F)
 Strip Length: 0.47" - 0.55" (12-14mm)
 Color: Blue/Transparent

STANDARDS & SPECIFICATIONS:




UL/cUL 486C, 467 Grounding - E5238
 CE Certified
 IEC/EN 60998
 RoHS Compliant
 UKCA
 UL 94 V2 Flame Rating

WIRE RANGE:

Conductor Type:	AWG (Metric)
Copper (Solid & Stranded)	10 – 22 AWG (0.5-6mm ²)
Solid Copper-Clad Aluminum	10 – 12 AWG
Stranded Copper Tin Bonded	10 – 22 AWG (0.5-6mm ²)

Listed for use with CU AND CC-CU. Do not use on Aluminum.

DIMENSIONS:



Dimension A	
2-Port	0.66 [16.8]
3-Port	0.94 [24]
5-Port	1.52 [38.6]

All dimensions are ±0.1"

Units: in [mm]

ORDERING INFO:

Catalog #	Model	Ports	Quantity	Weight Lbs. (Kg)
30-16L32	L32	2	Box of 1,000	8.11 (3.67)
30-16L33	L33	3	Box of 1,000	11.51 (5.22)
30-16L35	L35	5	Box of 500	9.44 (4.28)

FACTORY CONTACT:

IDEAL INDUSTRIES, INC.
 1375 Park Avenue; Sycamore, IL 60178
 Ph: (800) 324-9571
 Fax: (888) 222-6140
 E: oem@idealindustries.com

NOTES: